QUALITY REPORT

FOUNDATION AND STRUCTURE

- Reinforced concrete using isolated footings and unidirectional slabs according to Geotechnical Study.
- External staircase of straight development with reinforced concrete steps.
- Interior staircase of straight development with reinforced concrete steps.
- Concrete slab at the entrance to the house and at the entrance to the plot as a pergola.
- Concrete wall 25 cm insótano under running shoes, with screed.

EXTERIOR ENCLOSURE

- Facade enclosure finished SATE 60 + thermoclay **block** 14cm + mortar plaster 1cm + air chamber 2.5cm + rock wool 4cm + hollow brick 7cm + interior surface finish. Total thickness: 36cm.
- Facade enclosure finished SATE 100 + blockand thermoclay 14cm + mortar plaster 1cm + air chamber 2.5cm + rock wool 4cm + hollow brick 7cm + interior surface finish. Total thickness: 40cm.
- Porcelain **stoneware** + thermoclay block 14cm + mortar plaster 1cm + air chamber 2.5cm + rock wool 4cm + hollow brick 7cm + interior surface finish. Total thickness: 32cm.

COVER

- Non-passable flat with XPS insulation, with gravel finish. Space for air conditioning installations and pre-installation of solar panel.
- Solariumum passable porcelain stoneware finish type C3.

FACADE

- SATE white color.
- Porcelain stoneware or Sate black color according to design

INTERIOR PARTITIONS

• LHD brick 7 cm coated with plaster plaster + paint.

BATHROOM COVERINGS

- In 1st quality porcelain stoneware neutral color.
- Optional: stoneware decorative finish on a wall.

INTERIOR AND EXTERIOR FLOORING

- Interior, in 1st quality porcelain stoneware with skirting board in the same material.
- Exterior, in 1st quality porcelain stoneware, non-slip, of the same range as the flooring placed inside.

INTERIOR AND EXTERIOR LIGHTING

- Interior, LED lighting, porthole in ceiling in kitchen and plugs according to regulations.
- Exterior, Exterior wall lamps on façade according to exterior design,
 Optional: intelligent electric charging point for vehicle.

EXTERIOR CARPENTRY

- In aluminum with European seal and thermal break lacquered aluminum RAL 7011. Height 230cm and 210cm according to elevation plans.
- Aluminum entrance door RAL 7011, with security lock.

INTERIOR CARPENTRY

- Kitchen:
 - Furnished with lacquered high and low furniture, equipped with a stainless steel sink.
 - o Induction hob under bench, single-lever tap and Extractor of Classification A ++ of ceiling.
 - o Quartz countertop type Silestone or similar.

Passage doors:

o In wood smooth lacquered finish in light color (height 210), with design cranks in two finishes, steel and black color and hidden hardware. Folding and sliding.

• Cabinets:

 Sliding cabinet doors lacquered in white glue with mirror, choice customers Termination Interior of the cabinets with shelves, and hanging bar, adapted to the dimensions.

GLASSES

- In double glazed windows with air chamber, low emissive, according to CTE.
- Double sliding in living room-kitchen and bedrooms and tilt-and-turn in bathrooms and gallery.
- Translucent glass in bathrooms and gallery.
- Glass railing recessed in solarium and internal staircase.

SANITARY WARE AND TAPS

- Health
- W.C. White design color.
- Washbasin on countertop in furniture according to design
- Shower with resin tray and thermostatic taps finished in chrome or black
- Washbasin taps, chrome mixer and design negro

PAINTING

• Smooth type white color.

HEATING AND AIR CONDITIONING

- Pre-installation of air conditioning
- AirZone system (AACC zoning).
- Electric heater with Aerothermal System (NUOS 200 WIFI)
- Installation of simple air renewal with aerators (or heat recovery, to be decided by promoter).
- Pre-installation of solar panel or photovoltaic panel (to be decided by promoter).

FOREIGN

- Garden: Finish of white marble gravel, with departure available for gardening, lighting and chill out area and shower.
- Fence:
 - o Main access façade from public road of monolayer coated wall 1.00 m and steel fittings.
 - o Party walls: painted monolayer coated wall 1.50m,.
 - o Pedestrian and rolled access doors of galvanized sheet with "Z" profile in the same color as exterior carpentry.
- Concrete slabs of 100x50cm at the entrance to the plot.

SPECIAL EQUIPMENT

- **Pool:** 7 x 3 of water sheet with the same outdoor pavement or tile.
- Basic home automation system (optional):
 - Control of exterior lights.
 - General On/Off of the house: Enable/Disable lighting.
 - Fixed blank and neg ro control screenfor individual control of:
 - Outdoor lights
 - Enable/disable lights
 - Water cut
 - Technical alarms of flooding (3 zones) and fire.
 - Blinds control
 - AACC Programming
- Appliance package. NOT INCLUDED (refrigerator, oven, dishwasher, microwave, washer and dryer) optional

SUSPENDED CEILINGS

- Pladur, removable in bathrooms and gallery for registration of facilities.
- At 2.60 meters high in hallway, bedrooms and kitchen.
- At 2.40 or 2.50 in bathrooms and gallery.
- Inclined under sloping slab in living room.

BASEMENT

- Concrete wall with insulation and hollow brick + interior surface finish.
- Facade enclosure finished SATE 60 + thermoclay **block** 14cm + mortar plaster 1cm + air chamber 2.5cm + rock wool 4cm + hollow brick 7cm + interior surface finish. Total thickness: 36cm.
- Floor: XPS insulation and concrete finish
- Eplaster plaster on ceiling + white paint.
- Outdoor shredder next to bathroom and two pumps for evacuation of rainwater and feces.